

COLMASTER SERIES COLMASTER YELLOW 772

Description : Yellow masterbatch for coloring polyolefin.

Application : Blown Film, injection, blow molding

Carrier Resin : Polyethylene

Addition Level : 2 – 3 %

Physical Properties :

Item	Test Method	Unit	Product Specification
MFI	ASTM D – 1238 (190 °C / 2.16 kg)	g / 10 min	11 – 31
Specific Gravity	JIS K 7112	-	1.30 – 1.40
Moisture Content	ASTM D 6980-12	%	< 0.1
Heat resistance	Based on Pigment Specification	°C	<200
Light Fastness	Based on Pigment Specification	1 – 8	3
Weather Fastness	Based on Pigment Specification	1 – 5	-

Packaging

COLMASTER YELLOW 772 is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

Storage

COLMASTER YELLOW 772 should be stored in a dry environment. Opened bag should be kept tightly to prevent contamination of the product.

02/II/25/COL772

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of utilization of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.

PT INTERA LESTARI POLIMER

www.interapolimer.com

info@interapolimer.com

Jakarta
Jl. Kesehatan No. 48, Jakarta 10160
P : +62 21 38 901 901
F : +62 21 38 901 890

Bandung
Jl. Sukamenak No. 97 Bandung 40227
P : +62 22 8780 2277
F : +62 22 541 9594

Surabaya
Jl. Berbek Industri II No. 4, Sidoarjo 60293
P : +62 31 843 8484
F : +62 31 847 5350