

INTRAWHITE SERIES

INTRAWHITE 7102

Description	:	High-concentrated bluish white masterbatch
Application	:	Blown Film, Extrusion, Injection, Blown Molding
Carrier Resin	:	Polyethylene
Addition Level	:	2 – 3 %

Physical Properties

Item	Test Method	Unit	Product Specification
Melt Flow Index	ASTM D – 1238 (190°C / 2.16 kg)	g / 10 min	22 – 42
Specific Gravity	JIS K 7112	-	1.92 – 2.02
Moisture Content	ASTM D 6980-12	%	< 0.1
Resin Application	Based on Pigment Specification	-	PE, PP

Packaging

INTRAWHITE 7102 is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

Storage

INTRAWHITE 7102 should be stored in a dry environment, and not exceed 12 months for optimum performance. Opened bag should be kept tightly to prevent contamination of the product

01/II/25/7102

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of utilization of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.