



PT ECOBUKIT RECYCLE INDONESIA

PT ECOBUKIT RECYCLE INDONESIA

Subsidiary of PT Bukitmega Masabadi

Jl. Raya Cikarang – Cibarusah No. 83
Sukaresmi, Cikarang Selatan, Bekasi
Jawa Barat, 17857
INDONESIA

PRODUCT DATA SHEET

Procylen[®] LLD012



Product Code	:	LLD012
Product Grade	:	r - LLDPE Procylen LLD Film FFS
Product Format	:	Granule/Pellet
Description	:	LLD012 is a post-industrial recycled linear low-density polyethylene (LLDPE) characterized by a melt flow index of less than 3 (measured at 190°C, 2.16 kg) and exhibits a Light Grey appearance.
Application	:	Suitable for applications like compounding, extrusion and blow molding, including pipes, films, and bottles
Processing Temperature	:	From 180 to 220 °C
Packaging	:	Supplied in 25 kgs plastic woven bag.

Specification	Unit	Value	Method
Melt Index (190 °C/2.16 kg)	g/10 min	< 3.00	ASTM D 1238
Density	kg/cm ³	930 ± 0.5%	ASTM D 1505
Bulk Density	kg/m ³	500 – 6000	TM-BC-003
Moisture Content	%	Max. 0.1	TM-BC-002
Color	-	Light Grey	Visual
Odor	-	Barely perceptible	Olfactory
# Granule per gram	-	40 – 60	TM-BC-001

Storage	:	The container is tightly closed and stored in a cool, dry and dust free area and protected from direct sunlight and/or heat.
---------	---	--

Disclaimer: Procylen is a registered trademark of PT Ecobukit Recycle Indonesia. The information provided herein is based on our knowledge as of the specified date. Our technical recommendations apply exclusively to the indicated product and do not constitute a guarantee of specific quality. We advise customers to conduct their own tests to verify suitability and performance. This technical data sheet supersedes and replaces any prior versions.

Prepared by Product Stewardship

Version: 1.0, Issued date: July 14, 2026