



PT ECOBUKIT RECYCLE INDONESIA

PT ECOBUKIT RECYCLE INDONESIA

Subsidiary of PT Bukitmega Masabadi

Jl. Raya Cikarang – Cibusah No. 83
Sukaesmi, Cikarang Selatan, Bekasi
Jawa Barat, 17857
INDONESIA

PRODUCT DATA SHEET **PROCYLENE® LLD010**



Product Code	:	LLD010
Product Grade	:	r – LLDPE Natural Super MFI 3 – 5
Product Format	:	Granule/Pellet
Description	:	LLD010 is a post-industrial recycled linear low-density polyethylene (LLDPE) characterized by a medium flow grade with melt flow index ranging from 3 to 5 (at 190°C, 2.16 kg) and exhibits a color appearance comparable to commercially virgin LLDPE.
Application	:	Suitable for applications like extrusion, compounding & injection molding.
Processing Temperature	:	From 180 to 220 °C
Packaging	:	Supplied in 25 kgs plastic woven bag.

Specification	Unit	Value	Method
Melt Index (190 °C/2.16 kg)	g/10 min	3.00 – 5.00	ASTM D 1238
Density	kg/m ³	930 ± 0.5%	ASTM D 1505
Bulk Density	kg/m ³	500 – 600	TM-BC-003
Moisture Content	%	< 0.1	TM-BC-002
Color	-	Translucent	Visual
# Granule per gram	-	40 – 50	TM-BC-001

Storage : The container is tightly closed and stored in a cool, dry and dust free area and protected from direct sunlight and/or heat.

Disclaimer: Procyline is a registered trademark of PT Ecobukit Recycle Indonesia. The information provided herein is based on our knowledge as of the specified date. Our technical recommendations apply exclusively to the indicated product and do not constitute a guarantee of specific quality. We advise customers to conduct their own tests to verify suitability and performance. This technical data sheet supersedes and replaces any prior versions.

Prepared by Product Stewardship

Version: 1.0, Issued date: June 11, 2025