



TECHNICAL DATA SHEET

GENERAL

Product Name	:	PA 8336 P
Color	:	NATURAL
Product Description	:	PA 8336 P is a high performance nucleating agent for polyolefins, providing a range of benefits to polypropylene and polyethylene
Application	:	Injection Molding, Thermoforming, Extrusion Blow Molding, Rotomolding, Extrusion, Blown Film, etc
Recommended Doses	:	As Required

CHEMICAL AND PHYSICAL PROPERTIES

Base Resin	:	PP
Pellet Size	:	50 - 100 pcs/g
Bulk Density	:	0.80 - 1.50 g/cm ³
Melt Flow Rate	:	20 ± 10 g/10min
Process Temp.	:	190°C - 230°C
Food Contact Approval	:	YES

KEY FEATURES

1. Solving shrinkage/dimension problem in PP application
2. Improve cycle time in injection process
3. Improve optical properties in PP or PE

Data or recommendations are based on the extensive laboratory testing and / or application experience and trust to be a reliable indication of the expected results. However the data does not constitute as a guarantee, and is offered only as a guide to performance. Therefore, final approval and acceptance must be evaluated by the buyer.

P.T. Polycolor Prima Perkasa

Jl. Jababeka XVIIIA, Blok V No.83 B

Cikarang Industrial Estate, Bekasi 17530 - Indonesia

Approved for Released :



Pepen Supendi
Supervisor QC