

Specifications for NISSEI machine

Model	NSX220 – 50A (HYBRID X-PUMP TYPE)
Controller	VEDA
Main Power	Power Source : AC380V 50 Hz, 3 Phase 3 Wire

Optional Specifications	
1. Screw diameter	56 mm
2. Screw type	Standard
3. Srew tip	Standard
4. Barrel type	Standard
5. Barrel head	Standard
6. Nozzle type	Standard
7. Controller display language	English
8. Cooling water circuit	Not Included
9. Distribution valves	Standard
10. Water filter	Not Included
11. 3-layered indicator lamp (R-Y-G)	Red Only
12. Main power breaker	380 V 3 Phase 3 Wire
13. Electrical outlet	Not Included
14. Electrical outlet	Not Included
15. Instruction manual book	English
16. Mold clamp	Not Included
17. Tool Box	Not Included
18. Locating ring	120 mm
19. Insulation plate	T-Slot Platen
20. Ejector rod	Multifunctional Ejector 30 mm ; 5 rods equipped
21. Ejector plate return confirmation	No
22. Air Blow	Software + Circuit
23. Core pull	Software + Circuit
24. Valve gate interface	Not Included
25. Robot interface	Yes
26. Protect of setting condition	Yes
27. Manual centralized lubrication system	Not Included
28. Mounting pad	ELC Type