

BF25-H/BF30-H Hand Pallet Truck

Load capacity: 2500kg/3000kg









Effortless

Durable

Cost Effective

Outstanding Quality



Easy to Pull, Built to Last

Less pulling force

Effortless steering

High-quality, wear-resistant nylon and polyurethane wheels, with high load capacity, and smooth, effortless steering.

Less starting force to move a load

High-precision chassis with less starting force, easily handling loads of 2500 and 3000kg.

Smooth lifting and lowering

Rubber-coated handle, comfortable, non-slip grip and wear-resistant; Three lever control for easy operation; Standard with handle lever release and foot pedal release; Adjustable lowering speed;

Handle lever automatically returns to neutral position after release.

Quality and Durability



High-strength chassis with 100% automated robotic welding

Minimal welding deformation, high precision and consistency, guaranteed welding quality.

Reinforced top cap

Additional support structures to increase strength and extend lifespan.



Adjustable push rod If two forks are not balanced after one year use, push rod can be adjusted to make the forks back to same height.

Grooved V-block for extra reinforcement

High-quality, wear-resistant steer wheels and load wheels

Starting Force

OTHERS

STAX 🗙



Internal test based on polyurethane wheel

Reinforced forks

Additional stiffeners on back of the forks for increased load capacity. Grooved forks, with a 400kg increase in static load capacity compared to flat forks.



Enhanced Rocker Arm



Big opening space for load wheels

A big opening space for load wheels, offering enhanced protection for the wheels, push rod, and wheel forks.

Cost Effective

One-piece cast pump with guaranteed quality, durable and easy to service

Removable piston guide cap, easy to maintain and repair. Over 200,000 times mechanical tests on working life. Annual volume over 500,000 pieces, reliable with no oil leakage. Removable small pump core design for easier repair and service. Thickened steel spring for stronger elasticity and longer working life.

High-quality, high-standard electrostatic powder coating

High level appearance with thick coating, strong adhesion, high corrosion resistance and wear resistance.

- Easy to use and easy to service
- There is more to expect from Staxx, as we understand and respect customers' need for a product with excellent performance and lowest ownership cost



Wheel Options

Multiple options for wheels to suit different working conditions.



Strict Quality Control



100% pump inspection



Assembly line



Robotic welding



Pre-delivery inspection



Automatic powder coating



Solid packaging

Specifications

	MODEL				BF25-H			BF30-H	
FEATURE									
1.1	capacity		kg	2500			3000		
1.2	pump type			BF			BF		
WHEEL									
2.1	wheel (drive/load) type			PU/RU/Nylon			PU/RU/Nylon		
2.2	size of steering wheel	ΦD	mm	180*50	180*50	200*50	180*50	180*50	200*50
2.3	size of loading wheel(single wheel)	Φd	mm	74*93	80*93	80*93	74*93	80*93	80*93
2.4	size of loading wheel(double wheel)	Φd	mm	74*70	80*70	80*70	74*70	80*70	80*70
DIMENSIONS									
3.1	lifting height	h	mm	115			115		
3.2	max. fork height	Н	mm	195	200	200	195	200	200
3.3	min. fork height	H1	mm	75	85	85	75	85	85
3.4	fork outer width	W	mm	520/550/685			520/550/685		
3.5	fork length	L	mm	900/1100/1150/1220			900/1100/1150/1220		
3.6	fork width	S	mm	160			160		
3.7	steel thickness (after painting)		mm	3			3.75		
3.8	weight		kg	61.5~68.5			71~78.5		



Ningbo Staxx Material Handling Equipment Co.,Ltd.

First floor, No.10 Building, No.688 Jinda Road, Yinzhou District, Ningbo, China

Tel: 86-574-89217230 info@cnmhe.com www.staxxmhe.com



MAKE YOUR JOB EASIER