

SPECIFICATION of HOPPER DRYER



HHD-50HL

- Uniform hot air distribution, which increase the drying efficiency
- Equipped with all digital P.I.D controller
- Hopper and all the parts are stainless steel
- Hopper and lower part can be separated to facilitate maintenance and material change
- Equipped with over temperature protection which can avoid any accidents caused by human or mechanical failures
- HL type is equipped with main power switch, over temperature protection, LCD screen controller & weekly timer
- Optional: HLINK Networking, Double-layer insulation cylinder, Exhaust air filter/ Fan inlet filter/ Magnetic Base/ Magnetic frame/ Hot air recycling/ Ground frame/ Mobile collection bin/ Suction box

MODEL	HHD-25E	HHD-50E	HHD-100E	HHD-150E
SPECIFICATION				
LOADING CAPACITY	25 kg	50 kg	100 kg	150 kg
HEATING POWER	2.7 kW	3.9 kW	6.4 kW	7.8 kW
BLOWER POWER	0.14 kW	0.17 kW	0.35 kW	0.35 kW
WEIGHT	32 kg	43 kg	75 kg	82 KG
EXTERNAL DIMENSION				
H.	990 mm	1165 mm	1425 mm	1520 mm
H1.	945 mm	1075 mm	1220 mm	1325 mm
H2.	465 mm	530 mm	735 mm	785 mm
H3.	415 mm	480 mm	535 mm	580 mm
H4.	190 mm	195 mm	225 mm	240 mm
H5.	160 mm	160 mm	175 mm	175 mm
D.	490 mm	545 mm	685 mm	760 mm
Ød1.	350 mm	435 mm	550 mm	630 mm
Ød2.	61 mm	74 mm	81 mm	81 mm
W.	745 mm	865 mm	1040 mm	1105 mm
W1.	150 mm	160 mm	180 mm	180 mm
W2.	150 mm	160 mm	180 mm	180 mm

*Note:

The above loading capacity is based on the particle diameter 3-5 mm with bulk density about 0.65 kg/L standard plastic raw materials version. The standard voltage is 3Phase, 380V, 50Hz.

We reserve the right to change specifications without prior notice. For special needs please let us know!