

## PIKOLI ALP-6 AUTOMATIC LUBRICANT PUMP OIL

### DESCRIPTION AND FEATURES

**PIKOLI ALP-6** are long-life, premium Automatic Lubricants Pump Oil based on novel, proprietary technology for Plastic Injection Machine. They aims to reduce efficiency loss by reducing vibration and protect hardworking toggle and bushing parts with tough, tested lubricant and complete lubrication systems.

**PIKOLI ALP-6** incorporate the highest quality, thermally-stable synthetic esters fortified with premium non-detergent, ashless additives for maximum protection at high pressures and non-stop 24 hours injection operation where hydraulic oil typically break down.

### PERFORMANCE BENEFITS

- Improves toggle efficiency
- Less Oil Consumption
- Less carbon and deposits formation
- Excellent anti wears properties.
- Protect corrosion and rust.
- Prevents short supply in case of pipe damage or tube used-up

### TYPICAL INSPECTIONS

PROPERTIES	TEST METHOD	ALP-6
Density @30 °C	ASTM D-1298-85	0.778
Viscosity @40 °C	ASTM D-445	100.6
Viscosity @100 °C	ASTM D-445	12.3
Viscosity Index	ASTM D-2270	114
Colour	ASTM D-1500	RED
Flash Point, °C	ASTM D-92	240
Pour Point, °C	ASTM D-97	-25
Copper Strip Corrosion	ASTM D-130	1A
Rust test	Rust Test	Pass
Four Ball Test	ASTM D-4172	0.38