

Pikoli Toggle Grease Ep NLGI 0, 00, 000

DESCRIPTION AND FEATURES

PIKOLI TOGGLE GREASE EP NLGI 0,00,000 is extreme pressure type multipurpose grease, formulated with lithium 12 hydroxy stearate soap base, designed for moderate an heavy duty industrial application and providing excellent resistance against corrosion, heavy load and shock load on bearing, and also humid, moisturize condition at water closed locations. **PIKOLI TOGGLE GREASE EP NLGI 0,00,000** is semi-fluid and has a homogeneous structure, providing a good pumpability. Moreover, it has good anti-corrosion and anti-oxidation properties.

PERFORMANCE BENEFITS

- Excellent resistance against water, oxidation and air moisture.
- Prevent wear, rust and corrosion.
- Suitable for application in operating high temperature.
- High pressure, irregular shocking loads.
- Long life for the lubricated parts and low maintenance costs.
- Performance level DIN GP000H-30 ISO-L-XC(F)BCB000

TYPICAL INSPECTIONS

PROPERTIES	TEST METHOD	TYPICAL DATA		
NLGI	ASTM D-217	0	00	000
Penetration at 25°C	ASTM D-217	355/385	400/430	445/475
Texture	-	Smooth	Smooth	Smooth
Soap type	-	Lithium	Lithium	Lithium
Color	Visual	Natural	Natural	Natural
Dropping point, °C	ASTM D-556	180	170	160
Rust Test	-	Pass	Pass	pass
Timken OK Load, kg	Timken Test	18	18	18