

COLMASTER SERIES

COLMASTER GREEN P 88111 LF

Description : Transparent green masterbatch for coloring polyolefin

Application : Extrusion, Injection Molding

Carrier Resin : Homopolymer polypropylene

Addition Level : 2 – 3 %

Physical Properties :

Item	Test Method	Unit	Product Specification
MFI	ASTM D – 1238 (230 °C / 2.16 kg)	g / 10 min	34 – 50
Moisture Content	ASTM D 6980-12	%	< 0.1
Specific Gravity	JIS K 7112	-	0.85 – 0.93
Heat Resistance	Based on Pigment Specification	°C	200
Light Fastness	Based on Pigment Specification	1 - 8	7
Weather Fastness	Based on Pigment Specification	1 - 5	-
Resin Application	Based on Pigment Specification	-	PP

Packaging

COLMASTER GREEN P 88111 LF is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

Storage

Store in a cool dry place to prevent moisture absorption.

01/XI/25/COL88111PLF

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as condition and methods of utilization of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.