

# COLMASTER YELLOW 7941

- Description** : High concentration yellow masterbatch for coloring polyolefin.
- Application** : Blown Film, Blow Molding, Injection Molding, Extrusion
- Carrier Resin** : Polyethylene
- Addition Level** : 1 – 3 %
- Physical properties** :

Item	Test Method	Unit	Product Specification
MFI	ASTM D – 1238 ( 190 °C / 2.16 kg )	g / 10 min	17 – 23
Specific Gravity	JIS K 7112	-	1.22 – 1.28
Moisture Content	ASTM D 6980-12	%	< 0.1
Heat Resistance	Based on Pigment Specification	°C	< 200
Light Fastness	Based on Pigment Specification	1 – 8	4
Weather Fastness	Based on Pigment Specification	1 – 5	-
Resin Application	Based on Pigment Specification	-	LDPE, LLDPE, HDPE, PP

## Packaging

COLMASTER YELLOW 7941 is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

## Storage

COLMASTER YELLOW 7941 should be stored in a dry environment. Opened bag should be kept tightly to prevent contamination of the product.

**01/IX/21/COL7941**

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of utilization of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.