

SPECIFICATION

Product Name: Polyethylene Wax

CAS No. 9002-88-4

Grade: FW820

| No | Tests | Unit | Specifications | Test method |
|----|---------------------|--------------------|----------------|----------------|
| 1 | Softening point | °C | 100-105 | ASTM D6090-99 |
| 2 | Viscosity | CPS, 135°C | 5-10 | ASTM D1986-91 |
| 3 | Penetration | dmm, 25°C | ≤5 | ASTM D1321-02A |
| 4 | Thermal weight loss | % | ≤2 | ASTM D721 |
| 5 | Appearance | . | White | |
| 6 | Density | -g/cm ³ | 0.90-0.94 | |
| 6 | Physical form | | Powder\granule | |

Application: PVC, compound stabilizer, filler masterbatch, plastic, cable filler compound, coating, ink, paint, hot melt adhesive, shoe cream, lubricant, mold discharging agent, etc...

Packing: 25kg/bag, PP or paper bags

Declaration: the product is only used for industry, and the final data are based on the COA of the delivery products.

ADD:59 WAN AN WEST RD,JIANGNING DISTRICT, NANJING CITY, CHINA

T:+86-25-66049188 F:+86-25-52839992

SALES@FAER-WAX.COM WWW.FAER-WAX.COM