



PT ECOBUKIT RECYCLE INDONESIA

PT ECOBUKIT RECYCLE INDONESIA

Subsidiary of PT Bukitmega Masabadi

Jl. Raya Cikarang – Cibusrah No. 83
Sukaesmi, Cikarang Selatan, Bekasi
Jawa Barat, 17857
INDONESIA

PRODUCT DATA SHEET Procyline® HDE683



Product Code	:	HDE683
Product Grade	:	r - HDPE Natural Super MFI < 3
Product Format	:	Granule/Pellet
Description	:	HDE683 is a post-industrial recycled high-density polyethylene (HDPE) characterized by a melt flow index of less than 3 (measured at 190°C, 2.16 kg) and exhibits a colorless appearance, closely resembling commercially virgin HDPE.
Application	:	Suitable for applications like compounding, extrusion and blow molding, including pipes, films, and bottles
Processing Temperature	:	From 180 to 220 °C
Packaging	:	Supplied in 25 kgs plastic woven bag.

Specification	Unit	Value	Method
Melt Index (190 °C/2.16 kg)	g/10 min	< 3.00	ASTM D 1238
Density	kg/cm ³	960 ± 0.5%	ASTM D 1505
Bulk Density	kg/m ³	500 – 550	TM-BC-003
Moisture Content	%	< 0.1	TM-BC-002
Color	-	Colorless	Visual
# Granule per gram	-	40 – 50	TM-BC-001

Storage : The container is tightly closed and stored in a cool, dry and dust free area and protected from direct sunlight and/or heat.

Disclaimer: *Procyline is a registered trademark of PT Ecobukit Recycle Indonesia. The information provided herein is based on our knowledge as of the specified date. Our technical recommendations apply exclusively to the indicated product and do not constitute a guarantee of specific quality. We advise customers to conduct their own tests to verify suitability and performance. This technical data sheet supersedes and replaces any prior versions.*

Prepared by Product Stewardship

Version: 1.0, Issued date: February 11, 2025