

INTANOX PE 1068

Description : Anti Oxidant Masterbatch
Application : Blown film, Extrusion, Injection Molding, Blow Molding
Carrier Resin : Polyethylene
Addition Level : 1 - 4 %

Physical Properties

| ITEM | TEST METHOD | UNIT | PRODUCT SPECIFICATION |
|------------------|--------------------------------------|------------|-----------------------|
| Melt Flow Index | ASTM D – 1238 (190°C / 2.16 kg) | g / 10 min | 40 - 70 |
| Specific Gravity | JIS K 7112 | - | 0.85 – 0.95 |
| Moisture Content | ASTM D 6980-12 | % | < 0.1 |

Packaging

INTANOX PE-1068 is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

Storage

INTANOX PE-1068 should be stored in a dry environment. Opened bag should be kept tightly to prevent contamination of the product.

03/VI/21/INTANOX-PE1068

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of utilization of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.