

INTRAWHITE 10 P 60

- Description** : High-concentrated white masterbatch. INTRAWHITE 10 P 60 is especially suited for giving a high hiding power film/sheet extrusion at a low let down ratio.
- Application** : Blown Film, Extrusion, Injection, Blown Moulding
- Carrier Resin** : Polyethylene
- Addition Level** : 1 - 4 %

Physical Properties

Item	Test Method	Unit	Product Specification
Melt Flow Index	ASTM D – 1238 (190°C / 2.16 kg)	g / 10 min	30 – 50
Specific Gravity	JIS K 7112	-	1.63 – 1.73
Moisture Content	ASTM D 6980-12	%	< 0.1

Packaging

INTRAWHITE 10 P 60 is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

Storage

INTRAWHITE 10 P 60 should be stored in a dry environment, and not exceed 12 months for optimum performance. Opened bag should be kept tightly to prevent contamination of the product

03/VI/18/10P60

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of utilization of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.

PT INTERA LESTARI POLIMER

www.interapolimer.com

info@interapolimer.com

Jakarta
Jl. Kesehatan No. 48, Jakarta 10160
P : +62 21 38 901 901
F : +62 21 38 901 890

Bandung
Jl. Sukamenak No. 97 Bandung 40227
P : +62 22 8780 2277
F : +62 22 541 9594

Surabaya
Jl. Berbek Industri II No. 4, Sidoarjo 60293
P : +62 31 843 8484
F : +62 31 847 5350