

INTRAWHITE 10P75

- Description** : High-concentrated white masterbatch. Intrawhite 10P75 is especially suited for giving a high hiding power film/sheet extrusion at a low let down ratio.
- Application** : Blown Film, Extrusion, Injection, Blown Moulding
- Carrier Resin** : Polyethylene
- Addition Level** : 1 - 4 %

Physical Properties

Item	Test Method	Unit	Product Specification
MFI	ASTM D – 1238 (190 °C / 2.16 kg)	g / 10 min	15 - 35
Specific Gravity	JIS K 7112	-	2.08 – 2.18
Moisture Content	ASTM D 6980-12	%	< 0.1

Note : The above data are only nominal typical values and it should not be used for standard specification because these data are varied according to process conditions

Packaging

Intrawhite 10P75 is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

Storage

Intrawhite 10P75 should be stored in a dry environment, and not exceed 12 months for optimum performance. Opened bag should be kept tightly to prevent contamination of the product

04/V/20/10P75

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of utilization of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.