INTRAWHITE HDL 05

Description : White masterbatch contains high quality TiO_2.
Application : Film / sheet extrusion, blown film, blow moulding, injection moulding.
Carrier Resin : Polyethylene
Addition Level : 1 - 4 %

Physical Properties

Item	Test Method	Unit	Product Specification
Melt Flow Index	ASTM D – 1238 (190 ^{O}C / 2.16 kg)	g / 10 min	10 - 30
Specific Gravity	JIS K 7112	-	1.8 – 2
Moisture Content	ASTM D 6980-12	%	< 0.1

Packaging

Intrawhite HDL 05 is supplied in pellet form, in 25 kgs double layered bags, consisting of plastic PE bag as inner layer and PP woven laminated paper bag as outer layer.

Storage

Intrawhite HDL 05 should be stored in a dry environment, and not exceed 12 months for optimum performance. Opened bag should be kept tightly to prevent contamination of the product.

03/V/20/HDL05

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

PT INTERA LESTARI POLIMER
www.interapolimer.com | info@interapolimer.com

Jakarta
Jl. Kesehatan No. 48, Jakarta 10160
P : +62 21 38 901 901
F : +62 21 38 901 890

Bandung
Jl. Sukamenak No. 97 Bandung 40227
P : +62 22 8780 2277
F : +62 22 541 9594

Surabaya
Jl. Berbek Industri II No. 4, Sidoarjo 60293
P : +62 31 843 8484
F : +62 31 847 5350