



# PT HALIM SAMUDRA INTERUTAMA

SALES OFFICE ADDRESS : JL. TOMANG RAYA NO. 4 JAKARTA 11430 – INDONESIA  
TELP. : 021-5600400, 5660708 FAX. : 021-5600390, 5667440, E-mail : [hsp@halim-sakti.com](mailto:hsp@halim-sakti.com)  
FACTORY : JL. INDUSTRI RAYA IV BLOK AE NO. 10-BUNDER CIKUPA, KAB. TANGERANG, 15710 BANTEN-INDONESIA  
TELP. : 021-5903992 (HUNTING) , FAX. : 0215900268, E-mail : [hasiu@centrin.net.id](mailto:hasiu@centrin.net.id) , NPWP (TAX ID ) : 01.061.869.2-052.000

## TECHNICAL DATA SHEET NO. 027 S – QA / TER / VIII – 24 / 22

**COMMODITY** : HAIMASTER  
**GRADE** : MB  
**COLOR / NO. COLOR** : BLACK 95  
**APPEREANCE** : PELLET FORM  
**DATE** : AUGUST 24, 2022

### PHYSICAL PROPERTIES

TEST ITEM	UNIT	TEST METHOD	TEST VALUE
			BLACK 95
MELT INDEX (N TYPE 190°C , 10 Kg)	g/ 10 min.	ASTM D-1238	5 – 20
CARBON BLACK CONTENT	%	MAKER'S STD	50
PELLET SIZE	mm	MAKER'S STD	2 - 3
MOISTURE CONTENT	%	MAKER'S STD	MAX. 0.2
DISPERSION TEST	–	MAKER'S STD	PASS
CARRIER RESIN	--	-	LLDPE
APPLICATION	--	--	PP,PE INJECTION HDPE FILM/YARN PP FILM/YARN LLDPE FILM

- THESE TYPICAL PROPERTIES VALUES ARE INTENDED TO SERVE AS GUIDE ONLY, AND NOT AS SPECIFICATION LIMITS.

**QUALITY CONTROL DEPARTMENT**