



# PT HALIM SAMUDRA INTERUTAMA

SALES OFFICE ADDRESS : JL. TOMANG RAYA NO. 4 JAKARTA 11430 – INDONESIA  
TELP. : 021-5600400, 5660708 FAX. : 021-5600390, 5667440, E-mail : [hsp@halim-sakti.com](mailto:hsp@halim-sakti.com)  
FACTORY : JL. INDUSTRI RAYA IV BLOK AE NO. 10-BUNDER CIKUPA, KAB. TANGERANG, 15710 BANTEN-INDONESIA  
TELP. : 021-5903992 (HUNTING) , FAX. : 0215900268, E-mail : [hasiu@centrin.net.id](mailto:hasiu@centrin.net.id) , NPWP (TAX ID ) : 01.061.869.2-052.000

## TECHNICAL DATA SHEET

NO.020 S – QA / TER / VII – 24 / 22

COMMODITY : HAIMASTER  
GRADE : MB  
COLOR / NO. COLOR : WHITE 114  
APPEARANCE : PELLET FORM  
DATE : AUGUST 24, 2022

### PHYSICAL PROPERTIES

TEST ITEM	UNIT	TEST METHOD	TEST VALUE
			WHITE 114
MELT INDEX (E TYPE 190°C, 2.16 Kg)	g/ 10 min.	ASTM D-1238	3 – 12
PELLET SIZE	--	MAKER'S STD	2 – 3
MOISTURE CONTENT	%	MAKER'S STD	MAX. 0.2
DISPERSION TEST	--	MAKER'S STD	PASS
TiO2 CONTENT	--	MAKER'S STD	40
CARRIER RESIN	--	--	LLDPE
APPLICATION	--	--	PP,PE INJECTION HDPE FILM/YARN PP FILM/YARN LLDPE FILM

- THESE TYPICAL PROPERTIES VALUES ARE INTENDED TO SERVE AS GUIDE ONLY, AND NOT AS SPECIFICATION LIMITS.

QUALITY CONTROL DEPARTMENT