



PT ECOBUKIT RECYCLE INDONESIA

PT ECOBUKIT RECYCLE INDONESIA

Subsidiary of PT Bukitmega Masabadi

Jl. Raya Cikarang – Cibarusah No. 83
Sukaesmi, Cikarang Selatan, Bekasi
Jawa Barat, 17857
INDONESIA

PRODUCT DATA SHEET **PROCYLENE® PPL993**



Product Code	:	RMRPPL993
Product Grade	:	r – PP IP Natural Kw3 Homopolymer MFI > 10
Product Format	:	Granule/Pellet
Description	:	PPL993 is a post-industrial recycled homopolymer polypropylene (homo PP) characterized by a melt flow index exceeding 10 (measured at 230°C, 2.16 kg) and exhibits broad color variations from dark yellowish to dark greyish appearance
Application	:	Suitable for applications like extrusion, and injection molding, including films, yarn and appliance components.
Processing Temperature	:	From 180 to 250 °C.
Packaging	:	Supplied in 25 kgs plastic woven bag.

Specification	Unit	Value	Method
Melt Index (190 °C/2.16 kg)	g/10 min	> 10.00	ASTM D 1238
Density	kg/m ³	900 ± 0.5%	ASTM D 1505
Bulk Density	kg/m ³	500 – 600	TM-BC-003
Moisture Content	%	Max. 0.1	TM-BC-002
Color	-	Dark Yellow or Grey	Visual
Odor	-	Barely perceptible	Olfactory
# Granule per gram	-	30 – 50	TM-BC-001

Storage : The container is tightly closed and stored in a cool, dry and dust free area and protected from direct sunlight and/or heat.

Disclaimer: Procylenes is a registered trademark of PT Ecobukit Recycle Indonesia. The information provided herein is based on our knowledge as of the specified date. Our technical recommendations apply exclusively to the indicated product and do not constitute a guarantee of specific quality. We advise customers to conduct their own tests to verify suitability and performance. This technical data sheet supersedes and replaces any prior versions.

Prepared by Product Stewardship

Version: 1.0, Issued date: April 02, 2026