



VC-342

Electric Motor Cleaner

VC-342 merupakan bahan pembersih berbasis solven yang khusus dirancang untuk mencuci kotoran berupa minyak, debu, dan gemuk terutama yang terdapat pada peralatan seperti electromotor, generator, peralatan listrik, dll.

- Tidak terbakar
- Tidak korosif terhadap logam
- Cepat kering sehingga proses pembersihan lebih singkat.
- Efek terhadap insulasi, karet dan coating bervariasi, tes sebelum aplikasi sangat dianjurkan.

APLIKASI

Gunakan produk ini pada ruangan dengan ventilasi yang baik.

VC-342 dapat digunakan dengan cara perendaman, pencelupan, semprot, sikat, atau lap.

SPESIFIKASI

Rupa	: Cairan jernih
Titik Nyala	: Tidak ada
Specific Gravity	: 1,42 – 1,48

PENANGANAN

Gunakan kaca mata pelindung pada saat penanganan. Jangan menghirup uap produk ini. Pada beberapa kasus dapat menimbulkan mual dan pusing jika menghirup terlalu lama. Segera hirup udara segar dan bersih jika terasa gejala pusing dan mual.

Hindari kontak dengan mata, kulit atau pakaian. Tutup kembali kemasan dengan rapat setelah pemakaian.

KEMASAN

20 ltr/pail
25 ltr/pail

DESCRIPTION

VC-342 is a specially inhibited chlorinated organic solvent, used to clean oil, grease and dirt from electrical equipments such as motors and generators, circuit breakers, armatures, switches, bearings, distribution panels, machineries, instruments, etc.

VC-342 has, among others, the following features :

- Non-flammable.
- Non-corrosive to metals, including aluminum.
- Evaporates completely leaving no oily residue.
- Has no adverse effects on most insulations and coating normally found in electrical equipments. To ensure there will be no problem, however, spot test is highly recommended.

APPLICATION

Use VC-342 in a well ventilated area. VC-342 is easily applied as a soaking or dipping solution in a tank or bucket, it may be applied also by brushing, spraying with a spray gun, wiping with clean cloth. In many cases, it will not be necessary to disassemble the equipment to achieve thorough cleaning.

HANDLING PRECAUTIONS

Do not use VC-342 in a confined area. Do not inhale vapour. Excessive inhalation may cause nausea and dizziness. In case ill effects are apparent, move to an area where fresh air is plentiful and get medical treatment at once.

Avoid contact with eyes, skin or clothing. In case of contact, flush eyes with plenty of water for at least 10 minutes and get medical attention immediately.

Close tightly the container after use.