XYL-250S

Automatic Shrinkable Label Inserting Machine

全自動立式自動套標籤機



機械特性

1. 獨特豪華亮麗外觀造型，採用不銹鋼包覆設計，符合機械設計規範，單一機體安裝方便。
2. 機械設計採用模組化設計，拆裝更換方便迅速。
3. 所有調整模組，採用連動式設計，操作簡便，調整迅速。
4. 驅動系統使用精密齒輪設計，穩定的傳動速度，可達到標籤長度 ±1mm 公差要求。
5. 使用超音波電眼感應送料，配合彈簧張力控制系統，確保膜料輸送更穩定。
6. 使用大螢幕人機介面操控設計，更為貼近人性化機械操控方式。
7. 機台設計可依據套標長度設計，標長可至 300mm 以上。

Features

1. Machine constructed by stainless steel with especially and luxurious appearance. Conform to safety regulation. Single machine structure ensures convenient installation.
2. Modular design for quick change over.
3. All adjustable modular design by transmission type for easy operation and fast adjustment.
4. The accurate gear wheel design for driver system to stable the transmition speed and limit the label height within (+/-) 1mm tolerance.
5. Using supersonic sensor to detect sleeve and with spring tension controller system for ensuring the feeding sleeve steady.
6. The interface with large screen touch controller for user-friendly operation.
7. Machine design can fit the label height up to 300mm and above.

電源 Power source:	3P / 220V ~ 415V
生產速度 Production rate:	250 BPM (標籤長度180, label length 180 mm)
瓶罐直徑 Range of bottle diameter:	Ø25 ~ Ø125
套標長度 Label insertion length:	25 mm ~ 220 mm
標籤厚度 Range of label thickness:	0.035 ~ 0.08 mm
膜料材質 Material:	PVC, PET, OPS
總功率 Total Power:	4 KW
主機機械尺寸 Machine dimensions (L x W x H):	1190 x 980 x 2100 mm