XYL- 450L

Automatic Shrinkable
Label Inserting Machine

全自動立式自動套標籤機



機械特性

1. 獨特豪華亮麗外觀造型，採用不銹鋼包覆設計，符合機械設計規範，單一機體安裝方便。
2. 機械設計採用模組化設計，拆裝更換方便迅速。
3. 新型膜料儲料設計，使用精密滾輪傳送，配合滑軌升降機構，可達到每分鐘生產速度 450 瓶，標籤長度 100 mm 長，儲料 1 分鐘時間。
4. 快速接料系統，搭配膜料儲料設計，不需停機接料，提高生產效率。
5. 所有調整模組，採用連動式設計，操作簡便，調整迅速。
6. 驅動系統使用精密齒輪設計，穩定的傳動速度，可達到標籤長度 ±1mm 公差要求。
7. 使用超音波電眼感應送料，配合彈簧張力控制系統，確保膜料輸送更穩定。
8. 使用大螢幕彩色人機介面操控設計，更為貼近人性化機械操控方式。
9. 機台設計可依據套標長度設計，標長可至 300mm 以上。

電源 Power source:
生產速度 Production rate:
瓶罐直徑 Range of bottle diameter:
套標長度 Label insertion length:
標籤厚度 Range of label thickness:
膜料材質 Material:
總功率 Total Power:
主機機械尺寸 Machine dimensions (L x W x H):



Features

1. Machine constructed by stainless steel with especially and luxurious appearance. Conform to safety regulation. Single machine structure ensures convenient installation.
2. Modular design for quick changeover.
3. New accumulating label system use precision roller design with splicing system. One minute accumulating period to achieve the production speed up to 450 bpm on100 mm label height.
4. High speed splicing system enables reel change without machine to stop. Improve line productivity.
5. All adjustable modular parts require simple operation and minor adjustment.
6. The accurate gear wheel design for driver system to stable the transmition speed and limit the label height within (+/-) 1mm tolerance.
7. Using supersonic sensor to detect sleeve with the spring tension controller system to ensure feeding sleeve steady.
8. Colorful interface touch controller for friendly user operation.
9. Machine design can fit the label height up to 300mm and above.

3P / 220V ~ 415V	
450 BPM (標籤長度180, label length 180 mm)	
Ø25 ~ Ø125	
25 mm ~ 220 mm	
0.035 ~ 0.08 mm	
PVC, PET, OPS	
5 KW	
1190 x 1250 x 2100 mm	